

MS-01PON-S10-MP2

**4 x PoE+ Xpansion Power Module
for MP2 on board 4 x i226LM LAN**



Features

- 4 x PoE+ Xpansion Power Module for MP2 on board 4 x Intel® i226-LM 2.5G LAN
- Support IEEE 802.3 af/at
- IEEE 1588, PTP technology support

Specification

General

- Form Factor: Proprietary
- Input Connector: Xpansion slot (For MP2 Xpansion Power Socket)

Feature

- Support IEEE 802.3 af/at
- Single port maximum output power budget: 25.5W
- Total maximum output power budget: 50W
- Power Boost 50V~57V
- Support IEEE 1588, PTP technology

Environmental

- Operating Temperature: -40 ~ 85°C
(Depends on passive thermal solution)
- Storage Temperature: -40 ~ 85°C
- Operating Humidity: 10% ~ 90% R/H
(Non-condensing)

Software

- OS Support:
Microsoft® Windows® 11 IoT Enterprise LTSC 2024
Microsoft® Windows® 10 IoT Enterprise LTSC 2021
Ubuntu 24.04 / Linux Driver (by version and request)

Ordering Information

- Module Kit P/N: 5411N8610002, including
 - MS-01PON-S10-MP2 Xpansion Power Modules
 - Heatspreader with thermal pad
(Only for MP2 use)
 - Transfer bracket for MP2
 - Screw kit