


# MS-01PON-S10-MX2

**4 x PoE+ Xpansion Power Module  
for MX2 on board 4 x i226LM LAN**



## Features

- 4 x PoE+ Xpansion Power Module for MX2/MX2-D on board 4 x Intel® i226-LM 2.5G LAN
- Support IEEE 802.3 af/at
- IEEE 1588, PTP technology support

## Specification

### General

- Form Factor: Proprietary
- Input Connector: Xpansion slot (For MX2/MX2-D Xpansion Power Socket)

### Feature

- Support IEEE 802.3 af/at
- Single port maximum output power budget: 25.5W
- Total maximum output power budget: 50W
- Power Boost 50V~57V
- Support IEEE 1588, PTP technology

## Environmental

- Operating Temperature: -40 ~ 85°C  
(Depends on passive thermal solution)
- Storage Temperature: -40 ~ 85°C
- Operating Humidity: 10% ~ 90% R/H  
(Non-condensing)

## Software

- OS Support:  
Microsoft® Windows® 11 IoT Enterprise LTSC 2024  
Microsoft® Windows® 10 IoT Enterprise LTSC 2021  
Ubuntu 24.04 / Linux Driver (by version and request)

## Ordering Information

- Module Kit P/N: 5411N8600001, including
  - MS-01PON-S10-MX2 Xpansion Power Modules
  - Heatspreader with thermal pad  
(Only for MX2/MX2-D use)
  - Screw kit